



EasyWay-FP Micro Attendance and Access Control System having Fingerprint Scanner, provides secure platform against proxy punching and unauthorized entry.

#### FEATURES:

- ❖ Standalone Attendance & Access control System
- ❖ One touch identification - no need of PIN or Card
- ❖ Large storage capacity of 9,000 fingerprint templates
- ❖ 22, 000 Punch storage capacity
- ❖ Capacity of 2000 employee database with employee card number and employee name.
- ❖ Easy functions for finger registration.
- ❖ Configuration through keypad or software.
- ❖ Voice message indication for acceptance or rejection of finger
- ❖ Easy connection for door access
- ❖ On board TCP/IP Connectivity
- ❖ Round robin Memory

#### OPTIONAL FEATURES:

- ❖ Online Data Transfer

#### SOFTWARE:

- ❖ Proven software for all needs - for less than 10 employees to more than 5000 employees
- ❖ Windows based user friendly Transfer and MIS software
- ❖ Different software for Offices(without night shifts) and Factories having night shifts.
- ❖ Windows based customized payroll available with legal forms (Optional)

#### TECHNICAL SPECIFICATIONS:

<b>Sensor Type</b>	Optical
<b>Sensing Area</b>	16 X 19 (MM)
<b>Image Size</b>	280 X 320 pixels
<b>Verification Speed</b>	Less than 2 Seconds in 1:N condition
<b>F. R. R.</b>	Less than 0.1%
<b>F. A. R.</b>	Less than 0.001%
<b>Display-Type</b>	128 X 64 Graphic LCD with Backlight
<b>Display</b>	Date, Time, Card Number, Employee Name, Scrolling Message etc.
<b>Indicators</b>	3 LED for Power ON (Yellow), OK (Green) & Error (Red)
<b>Connectivity</b>	TCP/IP
<b>Voice Message</b>	Finger Print Read OK / Error
<b>Memory</b>	256K NV RAM, 22,000 punch storage capacity, 2,000 employee data base, up to 10 fingers per employee
<b>Battery Backup</b>	For RTC - Up to 1 year.
<b>Operating Voltage</b>	5 V DC / 1 Amp.
<b>Output</b>	One Relay (With NO & NC Contact)
<b>Keypad</b>	4 X 4 Numeric & Function Keys
<b>Size (H x W x D)</b>	183mm x 139mm x 50mm
<b>Mounting / Housing</b>	Wall Mounting / ABS housing
<b>Operating Environment</b>	Dust Free - Normal gate environment

#### OPTIONAL:

<b>UPS (No-load condition)</b>	Four hours battery backup for full operation
<b>Reader</b>	RFID / Smart Card Reader for 1:1 Verification
<b>Data Storage</b>	SDMMC Card Slot (1GB)

*Due to continuous product enhancements, specifications are subject to change without notice*



[www.apelectronicsindia.com](http://www.apelectronicsindia.com)

**AP Electronics**

49, Amrapali Society,  
B/h Amrapali Complex, Karelibaug,  
Vadodara 390 018. INDIA.

Ph. : +91 265 2490955 / 977

[info@apelectronicsindia.com](mailto:info@apelectronicsindia.com)